

according to Regulation (EC) No 1907/2006 (REACH) as amended

## **DYNAMAX DIESEL SYSTEM CLEAN & PROTECT**

Creation date 19th June 2023

Revision date Version 1.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier DYNAMAX DIESEL SYSTEM CLEAN & PROTECT

Substance / mixture mixture

UFI M00V-HE8X-110K-XTWV

Other mixture names

DYNAMAX ČISTENIE A OCHRANA DIESELOVÉHO SYSTÉMU

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

the preparation increases the protection of the fuel system against wear

Secondary uses

PC-FUE-5 Fuel additives and fuel components

Mixture uses advised against

The product should not be used in ways other then those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

**Supplier** 

Name or trade name DYNAMAX, s.r.o.

Address Alekšince 231, Alekšince, 95122

Slovakia

 Identification number (CRN)
 18049397

 VAT Reg No
 SK2020408808

 Phone
 +4210377822326

E-mail dynamax@dynamaxoil.com
Web address www.dynamaxoil.com

Competent person responsible for the safety data sheet

Name DYNAMAX, s.r.o.

E-mail dynamax@dynamaxoil.com

1.4. Emergency telephone number

European emergency number: 112

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

### Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d

Full text of all classifications and hazard statements is given in the section 16.

### Most serious adverse physico-chemical effects

Flammable liquid and vapour.

### Most serious adverse effects on human health and the environment

Suspected of damaging the unborn child. Causes skin irritation. Causes serious eye irritation.

### 2.2. Label elements

### **Hazard pictogram**







Signal word

Warning



according to Regulation (EC) No 1907/2006 (REACH) as amended

## **DYNAMAX DIESEL SYSTEM CLEAN & PROTECT**

Creation date 19th June 2023

Revision date Version 1.0

### **Hazardous substances**

Distillates (petroleum), hydro- treated light

toluene xylene

**Hazard statements** 

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

**Precautionary statements** 

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P370+P378 In case of fire: Use water mist to extinguish.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger.

### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

### **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 649-422-00-2 CAS: 64742-47-8 EC: 265-149-8 Registration number: 01-2119484819-18- xxxx	Distillates (petroleum), hydro- treated light	70-90	Asp. Tox. 1, H304	
Index: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 Registration number: 01-2119471310-51- xxxx	toluene	1-10	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Repr. 2, H361d STOT RE 2, H373	2, 3
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 Registration number: 01-2119488216-32- xxxx	xylene	1-10	Flam. Liq. 3, H226 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315	1, 2

### Notes

- 1 Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- 2 A substance for which exposure limits are set.
- 3 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.



according to Regulation (EC) No 1907/2006 (REACH) as amended

## **DYNAMAX DIESEL SYSTEM CLEAN & PROTECT**

Creation date 19th June 2023

Revision date Version 1.0

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

#### If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

#### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

#### If in eves

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

### If swallowed

Provide medical treatment. For persons with no symptoms, call the Toxicological Information Centre to decide about the need of medical treatment; provide information about the substances or composition of the product from the original packaging or the Safety Data Sheet of the product.

## 4.2. Most important symptoms and effects, both acute and delayed

#### If inhaled

Not expected.

### If on skin

Causes skin irritation.

## If in eyes

Causes serious eye irritation.

### If swallowed

Irritation, nausea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

### Unsuitable extinguishing media

Water - full jet.

## 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

## 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Prevent contact with skin and eyes.

### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.



according to Regulation (EC) No 1907/2006 (REACH) as amended

## **DYNAMAX DIESEL SYSTEM CLEAN & PROTECT**

Creation date 19th June 2023

Revision date Version 1.0

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

### 6.4. Reference to other sections

See the Section 7, 8 and 13.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Prevent contact with skin and eyes. No smoking. Obtain special instructions before use. Wash hands and exposed parts of the body thoroughly after handling. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

## The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

### 7.3. Specific end use(s)

not available

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

### **European Union**

## Commission Directive 2000/39/EC

Substance name (component)	Туре	Value	Note
	OEL 8 hours	221 mg/m <sup>3</sup>	
	OEL 8 hours 50 ppm		
xylene (CAS: 1330-20-7)	OEL 15 minutes	442 mg/m <sup>3</sup>	Skin
	OEL 15 minutes	100 ppm	

## **European Union**

## Commission Directive 2006/15/EC

Substance name (component)	Туре	Value	Note
	OEL 8 hours	192 mg/m <sup>3</sup>	
	OEL 8 hours	50 ppm	
toluene (CAS: 108-88-3)	OEL 15 minutes	384 mg/m³	Skin
	OEL 15 minutes	100 ppm	



according to Regulation (EC) No 1907/2006 (REACH) as amended

## **DYNAMAX DIESEL SYSTEM CLEAN & PROTECT**

Creation date 19th June 2023

Revision date Version 1.0

## 8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

#### Eye/face protection

Protective goggles.

## Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

## **Respiratory protection**

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

data not available

#### Thermal hazard

Not available.

### **Environmental exposure controls**

Observe usual measures for protection of the environment, see Section 6.2.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state liquid
Colour yellow
Odour characteristic
Melting point/freezing point data not available
Boiling point or initial boiling point and boiling range 35 °C
Flammability data not available
Lower and upper explosion limit data not available

23-55 °C Flash point Auto-ignition temperature data not available Decomposition temperature data not available data not available Kinematic viscosity data not available Solubility in water data not available Solubility in fats data not available Partition coefficient n-octanol/water (log value) data not available data not available Vapour pressure

Form liquid

Other information

Evaporation rate data not available

## **SECTION 10: Stability and reactivity**

Density and/or relative density

## 10.1. Reactivity

9.2.

not available

# 10.2. Chemical stability

The product is stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Unknown.



according to Regulation (EC) No 1907/2006 (REACH) as amended

## **DYNAMAX DIESEL SYSTEM CLEAN & PROTECT**

Creation date 19th June 2023

Revision date Version 1.0

#### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

### **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

## **Acute toxicity**

Based on available data the classification criteria are not met.

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data the classification criteria are not met.

### Carcinogenicity

Based on available data the classification criteria are not met.

## Reproductive toxicity

Suspected of damaging the unborn child.

### Toxicity for specific target organ - single exposure

Based on available data the classification criteria are not met.

### Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

### **Aspiration hazard**

Based on available data the classification criteria are not met.

### 11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### **SECTION 12: Ecological information**

## 12.1. Toxicity

**Acute toxicity** 

# 12.2. Persistence and degradability

not available

## 12.3. Bioaccumulative potential

Not available.

## 12.4. Mobility in soil

Not available.

## 12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

## 12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### 12.7. Other adverse effects

Not available.



according to Regulation (EC) No 1907/2006 (REACH) as amended

## **DYNAMAX DIESEL SYSTEM CLEAN & PROTECT**

Creation date 19th June 2023

Revision date Version 1.0

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

## Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

### Packaging waste type code

15 01 10 packaging containing residues of or contaminated by hazardous substances \*

(\*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

### **SECTION 14: Transport information**

14.1. UN number or ID number

UN 1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III - substances presenting low danger

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

### **Additional information**

Hazard identification No.

UN number

Classification code

Safety signs

30 1993

F1



## Marine transport - IMDG

EmS (emergency plan) MFAG F-E, S-E 310



according to Regulation (EC) No 1907/2006 (REACH) as amended

## **DYNAMAX DIESEL SYSTEM CLEAN & PROTECT**

Creation date 19th June 2023

Revision date Version 1.0

#### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

## Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

### toluene

Restriction	Conditions of restriction
	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than $0.1~\%$ by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

### 15.2. Chemical safety assessment

not available

#### **SECTION 16: Other information**

## A list of standard risk phrases used in the safety data sheet

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H312+H332 Harmful in contact with skin or if inhaled.

### Guidelines for safe handling used in the safety data sheet

P280 Wear protective gloves.

P202 Do not handle until all safety precautions have been read and understood.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P370+P378 In case of fire: Use water mist to extinguish.

### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

### Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by

road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

EC Identification code for each substance listed in EINECS

EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan EÚ European Union

EuPCS European Product Categorisation System IATA International Air Transport Association



according to Regulation (EC) No 1907/2006 (REACH) as amended

## **DYNAMAX DIESEL SYSTEM CLEAN & PROTECT**

Creation date 19th June 2023

Revision date Version 1.0

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

log Kow Octanol-water partition coefficient

MARPOL International Convention for the Prevention of Pollution from Ships

OEL Occupational Exposure Limits

PBT Persistent, Bioaccumulative and Toxic

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bioaccumulative

Acute Tox. Acute toxicity
Asp. Tox. Aspiration hazard
Eye Irrit. Eye irritation
Flam. Liq. Flammable liquid
Repr. Reproductive toxicity

Skin Irrit. Skin irritation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

### **Training guidelines**

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

## Recommended restrictions of use

not available

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

## More information

Classification procedure - calculation method.

## Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.