

TECHNICAL DATA SHEET

DYNAMAX ATF SYSTEM CLEANER

Date issued: 20.9.2024

1. Subject:

This product data sheet applies to the production, testing and delivery of the DYNAMAX ATF SYSTEM CLEANER additive.

Characteristics:

DYNAMAX ATF SYSTEM CLEANER - high performance cleaner for automatic transmissions with or without torque converter, suitable for all types of 4-8 speed transmissions. Removes pollution and deposits caused by operation, protects against corrosion and premature wear.

Appearance:

DYNAMAX ATF SYSTEM CLEANER is a liquid, yellow with a weak opalescence.

Usage:

- 1) To the automatic transmission - before changing the transmission oil.
- 2) Start the engine for approx. 15 min with frequent load changes (all gearbox positions).
- 3) Change the transmission oil and filter according to the manufacturer's instructions.

300 ml of additive is enough for 8 l of capacity. For larger capacities, add 40 ml of additive per liter of transmission oil. Change interval – every time the gear oil is changed

2. Technical parameters

DYNAMAX ATF SYSTEM CLEANER must comply with the following specifications:

Physical state	liquid
Colour	yellow
Odour	characteristic
Relative density [g.cm⁻³]	0,814
Boiling Point [°C]	180 - 250
Flash Point [°C]	>65

Specification variations in these characteristics may occur. Further informations to be available by SDS.

TECHNICAL DATA SHEET

Date issued: 20.9.2024

3. Storage:

DYNAMAX ATF SYSTEM CLEANER must be stored in closed, sealed containers in a dry, well-ventilated and cool warehouse protected from the weather. Do not expose to direct sunlight.

4. Delivery:

The method of delivery and the method of transport of DYNAMAX ATF SYSTEM CLEANER is the subject of the purchase contract, but it must be in accordance with the given regulations.

Contact office for information of a marketing nature:

DYNAMAX, s.r.o.
951 22 Alekšince 231
Tel./fax: 00421/37 78 22 326-7
www.dynamaxoil.com