

## TECHNICAL DATA SHEET

### DYNAMAX DIESEL SYSTEM CLEAN & PROTECT

Date issued: 20.9.2024

#### **1. Subject:**

This technical product sheet applies to the production, testing and delivery of the DYNAMAX DIESEL SYSTEM CLEAN & PROTECT additive.

#### **Characteristics:**

DYNAMAX DIESEL SYSTEM CLEAN & PROTECT - contains a selected combination of active substances to protect the fuel system against wear. Effectively dissolves deposits and residues of carbon, oil and soot. It ensures long-term lubrication of the injection pump and all moving parts. The preparation is also suitable for high-pressure systems with direct injection and the Common rail system.

#### **Appearance:**

DYNAMAX DIESEL SYSTEM CLEAN & PROTECT is a liquid, yellow with a weak opalescence.

#### **Usage:**

Pour into the fuel tank before refueling. Dosage: 300 ml per 60 l diesel every 6 months. Cleaning fluid is not a substitute for fuel!

#### **2. Technical parameters**

DYNAMAX DIESEL SYSTEM CLEAN & PROTECT must comply with the following specifications:

<b>Physical state</b>	liquid
<b>Colour</b>	yellow
<b>Odour</b>	characteristic
<b>Boiling Point [°C]</b>	35
<b>Flash Point [°C]</b>	23 - 55

Specification variations in these characteristics may occur. Further informations to be available by SDS.

---

## TECHNICAL DATA SHEET

Date issued: 20.9.2024

---

### **3. Storage:**

DYNAMAX DIESEL SYSTEM CLEAN & PROTECT must be stored in closed, sealed containers in a dry, well-ventilated and cool warehouse protected from the weather. Do not expose to direct sunlight.

### **4. Delivery:**

The method of delivery and the method of transport of DYNAMAX DIESEL SYSTEM CLEAN & PROTECT is the subject of the purchase contract, but must be in accordance with the given regulations.

### **Contact office for information of a marketing nature:**

DYNAMAX, s.r.o.  
951 22 Alekšince 231  
Tel./fax: 00421/37 78 22 326-7  
www.dynamaxoil.com