

TECHNICAL DATA SHEET

DYNAMAX OIL SYSTEM CLEANER

Date issued: 20.9.2024

1. Subject TL

This product data sheet applies to the production, testing and delivery of the DYNAMAX OIL SYSTEM CLEANER additive.

Characteristics:

DYNAMAX OIL SYSTEM CLEANER - the preparation is used to remove deposits and dirt settled in the oil system, thereby restoring the compression of the piston rings. It cleans the valves and thereby reduces noise and increases combustion efficiency.

Appearance:

DYNAMAX OIL SYSTEM CLEANER is a liquid, green with a weak opalescence.

Usage:

300 ml for 5 l of oil. The preparation is applied by pouring it into old oil with the engine off. It is then allowed to idle for 15-20 min. Finally, the oil is drained and the oil filter is replaced.

2. Technical parameters

DYNAMAX OIL SYSTEM CLEANER must comply with the following specifications:

Physical state	liquid
Colour	green
Odour	characteristic
Relative density [g.cm⁻³]	0,800
Boiling Point [°C]	150 - 230
Flash Point [°C]	>61

Specification variations in these characteristics may occur. Further informations to be available by SDS.

TECHNICAL DATA SHEET

Date issued: 20.9.2024

3. Storage:

DYNAMAX OIL SYSTEM CLEANER must be stored in closed, sealed packages in a dry, well-ventilated and cool warehouse protected from the weather. Do not expose to direct sunlight.

4. Delivery:

The method of delivery and the method of transport of DYNAMAX OIL SYSTEM CLEANER is the subject of the purchase contract, but must be in accordance with the given regulations.

Contact office for information of a marketing nature:

DYNAMAX, s.r.o.
951 22 Alekšince 231
Tel./fax: 00421/37 78 22 326-7
www.dynamaxoil.com