

TECHNICAL DATA SHEET

DYNAMAX SL PLUS 20W/50

Date issued: 06.06.2024

1. Product description

DYNAMAX SL PLUS 20W/50 is a high performance mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers.

DYNAMAX SL PLUS 20W/50 is based on high performance virgin mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.

Use:

DYNAMAX SL PLUS 20W/50 is suitable for modern gasoline, diesel and LPG engines of passenger cars and vans with or without supercharging.

Specification:

SAE 20W/50
API SL/CF ACEA A3/B3

Approvals:

VW 505.00, MB 229.1

2. Technical parameters

Kinematic viscosity at 100°C, mm ² /s	typical value	17
Kinematic viscosity at 40°C, mm ² /s	typical value	150,5
Viscosity index	min.	122
Density at 15°C, kg/m ³	typical value	890
Pour point, °C	max.	-33
Flash point (COC), °C	min.	200

Specification variations in these characteristics may occur. Further informations to be available by SDS.