

TECHNICAL DATA SHEET

DYNAMAX ULTRA PLUS PD 5W/40

Date issued: 03.06.2024

Motor Oil

1. Product description

DYNAMAX ULTRA PLUS PD is a very low emission fully synthetic engine oil meeting mid SAPS (Sulphated Ash, Phosphorus & Sulphur) requirements.

DYNAMAX ULTRA PLUS PD is developed to extend engine life and maintain efficiency of the after treatment devices used in the latest generation passenger cars with gasoline & diesel engines.

DYNAMAX ULTRA PLUS PD reduces ash build up in diesel particulate filters (DPFs).

Use:

DYNAMAX ULTRA PLUS PD is strongly recommended for the latest generation high performance gasoline-, LPG- and diesel fuelled engines in passenger cars and light commercial vehicles requiring ACEA C3 oils which have to meet EURO 4-emission standards.

Specification:

SAE 5W/40
ACEA A3/B4/C3
API SN/CF

Approvals:

MB 229.51; MB 226.5; Ford WSSM2C917-A
VW 502.00/505.00/505.01; BMW Longlife-04
Porsche A40; GM DEXOS 2

2. Technical parameters

Kinematic viscosity at 100°C, mm ² /s	typical value	12,9
Kinematic viscosity at 40°C, mm ² /s	typical value	88
Viscosity index	min.	175
Density at 15°C, kg/m ³	typical value	849
Pour point, °C	max.	-39
Flash point (COC), °C	min.	241

Specification variations in these characteristics may occur. Further informations to be available by SDS.