

TECHNICAL DATA SHEET

DYNAMAX COOL ULTRA G12 -8

Dátum: 31.01.2023

1. Product description:

DYNAMAX COOL ULTRA G12 -8 is a cooling liquid based on ethylene glycol. It is designed to coolers of modern aluminium and cast-iron cooling systems of combustion engines. DYNAMAX COOL ULTRA G12 -8 protects the car year-round cooling system from the action of frost and corrosion. It provides very good heat transfer. Includes high-inhibitors corrosion protection for cooling system. Meets VW TL 774 D-F.

Use:

DYNAMAX COOL ULTRA G12 -8 is used for cooling systems for internal combustion engines. DYNAMAX COOL ULTRA G12 -8 serves as a full replacement for the coolant, which are made based on 1,2 - ethylene glycol (or glycol). Compatible with metal materials. Application: Undiluted pour into the radiator system. Painted surfaces should be sprayed with water after.

2. Technical parameters:

| | |
|---|----------------|
| Physical state | liquid |
| Colour | green |
| Odour | odorless |
| Freezing point, °C | - 8 +/- 1°C |
| Density at 20°C, kg/m ³ | 1,030 - 1,040 |
| Solubility in water, g.l ⁻¹ | soluble |
| Solubility in solvents, g.l ⁻¹ | alcohol, ether |

Specification variations in these characteristics may occur. Further informations to be available by SDS.

Product of:

DYNAMAX, s.r.o.
951 22 Alekšince 231
Tel./fax: 00421/37 78 22 326-7
www.dynamaxoil.com